



BI-PIN T1 BPC SPÉCIALE PINS RIGIDES
 Ø 3,17 x 10 mm - Pin Spacing 3,17 mm


CODE STOCK PART NUMBER	RÉFÉRENCE	CODE US US CODE	VOLTS	mA	MSCP ±25%	DURÉE DE VIE AC LIFE	FILAMENT
018152	OR 685 BPC		5	60	0,05	40 000	C2R
018153	OR 7714 BPC	7714	5	75	0,09	40 000	C2R
018154	OR 1099 BPC		12	60	0,15	16 000	C2F
018160	OR 856 BPC		28	24	0,15	16 000	CC2F

BI-PIN T1 1/4 PINS RIGIDES
 Ø 4,2 x 14 mm - Pin Spacing 2,54 mm


CODE STOCK PART NUMBER	RÉFÉRENCE	CODE US US CODE	VOLTS	mA	MSCP ±25%	DURÉE DE VIE AC LIFE	FILAMENT
018180	OR 585 BP	7583	5	60	0,05	100 000	C2R
018182	OR 7715 BP		5	115	0,15	40 000	C2R
018200	OR 4015 BP	7309	6	60	0,13	3 000	C2R
018210	OR 628 BP		6	200	0,63	1 000	C2R
018220	OR 4032 BP		12	40	0,12	10 000	C2F
018221	OR 7646 BP	7646	14	80	0,50	1 000	C2F
018320	OR 4097 BPE		16	30	0,034	25 000	C2F
018250	OR 4060 BP		24	35	0,13	25 000	C2F
018252	OR 619 BP		28	24	0,15	10 000	C2F
018260	OR 632 BP	7632	28	40	0,34	4 000	C2F
018273	OR 7590 BP		48	25	0,20	5 000	CC2F
018275	OR 7692 BP		60	20	0,15	5 000	CC2F