


AV35

## BI-PIN T1 3/4 PINS RIGIDES

Ø 6 x 16 mm - Pin Spacing 3,17 mm




CODE STOCK PART NUMBER	RÉFÉRENCE	CODE US US CODE	VOLTS	mA	MSCP ±25%	DURÉE DE VIE AC LIFE	FILAMENT
018280	<b>OR 783 BP</b>	7783	5	60	0,05	100 000	C2R
018285	<b>OR 362 BP</b>	7362	5	115	0,15	20 000	C2R
018290	<b>OR 380 BP</b>	7380	6,3	40	0,03	50 000	C2V
018300	<b>OR 381 BP</b>	7381	6,3	200	0,40	20 000	C2F
018302	<b>OR 7371 BP</b>	7371	12	40	0,12	10 000	C2V
018304	<b>OR 6038 BP</b>		12	60	0,15	16 000	C2V
018310	<b>OR 382 BP</b>	7382	14	80	0,30	50 000	C2F
018400	<b>OR 387 BP</b>	7387	28	40	0,30	25 000	C2F
018411	<b>OR 7461 BP</b>		48	25	0,20	5 000	CC2F
018421	<b>OR 7476 BP</b>		60	20	0,15	5 000	CC2F

AV36

## MINIATURE 2 PINS (US TYPE)

Ø 11,7 x 24 mm



CODE STOCK PART NUMBER	RÉFÉRENCE	VOLTS	mA	MSCP ±25%	DURÉE DE VIE AC LIFE	FILAMENT
019897	<b>GE 10*</b>	2,5	500	0,5	3 000	C6

\* En cours d'abandon.

\* To be discontinued.