



CODE STOCK PART NUMBER	RÉFÉRENCE	CODE US US CODE	Volts	mA	Watts	DURÉE DE VIE AC LIFE	FILAMENT
115056	E 1800	1800	1,35	60	0,08	500	S2
115057	E 3049	48	2	60	0,12	1 000	S2
115058	E 3043		2,5	500	1,25	3 000	C2R
115055	E 3439		5	90	0,45	1 500	C2V
115060	E 3065		6	50	0,3	2 000	C2V
115062	E 3411	411	6	60	0,36	10 000	C2R
115070	E 3061		6	100	0,6	2 000	C2V
115075	E 3069		6	180	1,1	2 000	C2V
115079	E 3451		6	250	1,5	2 000	C2R
115080	E 3450		6	350	2	2 000	C2V
115088	E 3452		6	500	3	1 000	C2R
115100	E 3470		6	700	4	1 000	C2R
115102	E 3040	40	6,3	150	1	3 000	C2R
115104	E 3046	46	6,3	250	1,6	3 000	C2R
115077	E 3066		6,5	100	0,65	2 000	C2V
115076	E 3072		6,5	150	1	2 000	C2V
115085	E 3068		6,5	300	2	2 000	C2A
115110	E 3510		7	100	0,7	2 000	C2V
115122	E 3341		7	300	2,1	2 000	C2R
115124	E 3020		10	50	0,5	2 000	C2V
115130	E 3022		12	20	0,24	1 000	C2V
115140	E 3025		12	50	0,6	1 000	C2V
115150	E 3353		12	100	1,2	1 000	C2V
115152	E 3354		12	120	1,44	1 000	C2V
115160	E 3453		12	170	2	2 000	C2V
115162	E 1309	1309	12	183	2,2	3 000	C2V
115165	E 3023		12	250	3	2 000	C2R
115170	E 3893		12	340	4	1 000	C2R
115175	E 3032		14	80	1,1	1 000	C2V
115177	E 1487	1487	14	200	2,8	2 000	C2V
115190	E 3018		18	20	0,36	1 000	C2V
115192	E 3033		18	100	1,8	1 000	C2V
115195	E 3044		18	166	3	1000	C2V
115210	E 3045		24	50	1,2	1 000	C2F
115230	E 3456		24	85	2	2 000	C2F
115240	E 3041		24	125	3	1 000	C2F
115250	E 3476		24	170	4	1 000	C2F
115258	E 3477		24	210	5	1 000	C2F
115260	E 3027		27	75	2	1 000	C2F
115330	E 3028		28	40	1,12	1 000	C2F