



CODE STOCK PART NUMBER	RÉFÉRENCE	VOLTS	WATTS	FLUX LUMENS	DURÉE DE VIE AC LIFE	DIMENSIONS D x L (MM)
---------------------------	-----------	-------	-------	----------------	-------------------------	--------------------------

GAMME PROFESSIONNELLE / Professional quality

131196	H 624300	24*	300		100	11 x 118
131197	H 624500	24*	500		100	11 x 118
131167	H 61107 R	230/240	200	3 200	2 000	11 x 118
131169	H 61109 R	230/240	300	5 000	2 000	11 x 118
131173	H 64702 R	230/240	500	9 500	2 000	11 x 118
131927	H 64740 R	230/240	1 000	22 000	2 000	11 x 192
131181	H 64760 R	230/240	1 000		2 000	11 x 254
131199	H 61103 R	230/240	1 500	33 000	2 000	11 x 254
132164	H 61104 R	230/240	2 000		2 000	11 x 332

BLUE LINE

BAS VOLTAGES / LOW VOLTAGES

24 V

131171	H 624150	24*	150		100	11 x 118
131179	H 624200	24*	200		100	11 x 118

28 V

131219	H 628200	28*	200		100	11 x 118
131221	H 628300	28*	300		100	11 x 118

42 V

131998	H 641150	42*	150		100	11 x 118
131997	H 642200	42*	200		100	11 x 118
132165	H 641250	42*	250		100	11 x 118
131992	H 642300	42*	300		100	12 x 118
131926	H 641500	42*	500		100	12 x 118

120 V/130 V

131999	H 648075	120/130	75	-	2 000	11 x 80
131975	H 64689	120/130	100	1 500	2 000	11 x 80
131976	H 64694	120/130	150	2 300	2 000	11 x 80
131161	H 61121	120/130	200	3 500	2 000	11 x 80
131191	H 61123	120/130	250	4 400	2 000	11 x 80
132000	H 641875	120/130	75	-	2 000	11 x 118
131192	H 62103	120/130	100	1 850	2 000	11 x 118
131164	H 61102	120/130	150	2 200	2 000	11 x 118
130157	H 61108	120/130	200	3 500	2 000	11 x 118
131166	H 61124	120/130	250	4 400	2 000	11 x 118
131170	H 61128	120/130	300	5 500	2 000	11 x 118
130163	H 61130	120/130	500	10 450	2 000	11 x 118
130165	H 61134	120/130	750	15 000	2 000	11 x 192

* Durée de vie moyenne constatée sur la base d'une tension régulée de 24 VAC, 28 VAC et 42 VAC.

* Average life time for constant regulated input voltage of 24 VAC, 28 VAC or 42VAC.