



- Pour luminaire fermé

- For fixture with protection glass

CODE STOCK PART NUMBER	RÉFÉRENCE	WATTS	DIMENSIONS D x L (MM)	IRC	TEMP. COUL. ° KEVIN	FLUX LUMENS	TENSION D'AMORCAGE STARTING V. (KVS)	COMPENSATION À 50 HZ u F	EQUIVALENCE
---------------------------	-----------	-------	--------------------------	-----	------------------------	----------------	---	-----------------------------	-------------

**AMORCEUR EXTERNE / External Ignitor**

D3/18

008475	<b>LD 2240</b>	150	47 x 211	85	3 000	13 500	2 R-5		CDM TT/ CMH-TT
008490	<b>LD 2140</b>	250	46 x 225	90	5 400	20 000	3-4,5	32	HQI-T/HIT HPIT-Plus
008574	<b>LD 2154</b>	250	57 x 248	65	4 400	20 000	0,8	20	HQIT-NSI*
008492	<b>LD 2142</b>	400	46 x 275		5 200	32 000	3 A		HIT
008427	<b>LD 2242</b>	400	46 x 275	65	3 800	34 000	3-4,5	45	HQIT-N
008396	<b>LD 2139</b>	400	62 x 275	93	5 200	32 000	3-4,5	45	HQI-BT
008575	<b>LD 2155</b>	400	57 x 248	65	4 400	31 000	0,8	31,5	HQIT-NSI*
008494	<b>LD 2144</b>	1 000	66 x 382	65	4 300	85 000	0,56-5	-	HPIT-PRO
008329	<b>LD 2144 OS</b>	1 000	76 x 340	93	6 000	80 000	4-5	85	HQIT/HIT
008545	<b>LD 2146</b>	2 000	100 x 430	93	5 200	180 000	4-5	60	HQIT
008402	<b>LD 2128</b>	3 500	100 x 430	93	5 200	320 000	4-5	100	HQIT

**AMORCEUR INTERNE / Integrated Ignitor**

008517	<b>LD 2145</b>	2 000	100 x 430	60	4 200	200 000	SANS/No	37	HQI-T/N
--------	----------------	-------	-----------	----	-------	---------	---------	----	---------

Autres teintes sur demande.

\*Amorçeur requis 0,9 à 1,3 KVS.

Other colors upon request.

\*Ignitor 0,9 à 1,3 KVS.

D3/15 D3/18



10 000°K : permet de recréer une lumière similaire à celle des fonds marins (à environ 5 m de profondeur)

Favorise la pousse du corail

10 000°K : creates same light conditions than in ocean (in water-depth of roughly 5 m)

Stimulates growth of corals

CODE STOCK PART NUMBER	RÉFÉRENCE	WATTS	DIMENSIONS D x L (MM)	CULOT BASE	TEMP. COUL. ° KEVIN	TENSION D'AMORCAGE STARTING V. (KVS)	POSITION D'ÉCLAIRAGE BURNING POSITION	EQUIVALENCE
008387	<b>LD 2138</b>	150	40 x 155	E27	6 500	1,9 A	U	MT 150 D
008421	<b>LD 2160</b>	250	46 x 225	E40	10 000			HIT
008399	<b>LD 2136</b>	400	46 x 275	E40	10 000	2,8	U	HIT
008400	<b>LD 2137</b>	1 000	76 x 340	E40	10 000	2,8	P60	HIT