


CODE STOCK PART NUMBER	RÉFÉRENCE	CODE ANSI	VOLTS	WATTS	TEMP. COUL. ° KELVIN	DISTANCE MONTAGE CONSEILLÉE (MM)	DURÉE AC LIFE	APPLICATIONS PRINCIPALES
130264	<b>H 164607</b>	EFM A1/229	8	50	3 300	32	50	FILMS ÉTROITS
130266	<b>H 164615</b>	EFN A1/230	12	75	3 350	32	50	FILMS ÉTROITS
130267	<b>H 646150S</b>	EFN	12	75	3 350	32	50	FILMS ÉTROITS
130269	<b>H 164627</b>	EFP A1/231	12	100	3 350	32	50	FILMS ÉTROITS
130259	<b>H 161479</b>		12	100	-	32	1 500	FILMS ÉTROITS
130270	<b>H 164634</b>	EFR A1/232	15	150	3 350	32	50	FILMS ÉTROITS
130295	<b>H 68139</b>		12	75	3 400	70	25	FILMS ÉTROITS
130272	<b>H 61480</b>	A1/246	24	250	3 100	32	50	FILM 16 MM



CODE STOCK PART NUMBER	RÉFÉRENCE	CODE ANSI	VOLTS	WATTS	TEMP. COUL. ° KELVIN	DISTANCE MONTAGE CONSEILLÉE (MM)	DURÉE AC LIFE	APPLICATIONS PRINCIPALES
130291	<b>H 63080</b>	ELS/ELR	16	50	3 100	120	650	MICROFILM
130293	<b>H 63082</b>	EPG	21	80	3 300	83	100	PROJ. 8 MM
130296	<b>H 63164</b>	ELE/ELT	30	80	3 450	83	20	PROJ. 8 MM
130299	<b>H 63090</b>	BHB	120	250	3 350	67	25	PROJ. 16 MM