


Sans miroir intérieur
(culot à 4 ergots + 1 plot central)

Without internal mirror

CODE STOCK PART NUMBER	RÉFÉRENCE	CODE ANSI	VOLTS	WATTS	DISTANCE FOCALE (C)	DIMENSIONS D x L (MM)	DURÉE AC LIFE	FIGURE N° DRAWING N°
130430	H 88224	CYN A1/212	24	150	39,7	32 x 103	25	3
130432	H 88295	CTD A1/182	230	150	33,4	29 x 76	25	1
130434	H 88597	CSF A1/178	230	300	39,7	32 x 103	25	2
130436	H 88897	DBS A1/180	230	500	39,7	32 x 103	25	2
130438	H 67206	CWA A1/206	230	750	39,7	39 x 118	25	2
130440	H 67207	A1/207	230	1 000	39,7	39 x 118	25	2

(i) GX17Q : basse tension/low voltage.
G17Q : 230 V.



Avec miroir intérieur
(culot à 3 ergots + 1 plot central)

With internal mirror

CODE STOCK PART NUMBER	RÉFÉRENCE	CODE ANSI	VOLTS	WATTS	DISTANCE FOCALE (C)	DIMENSIONS D x L (MM)	DURÉE AC LIFE
130442	H 21240	EPS A1/240	230	300	39,7	15 x 87	50
130446	H 21268 (1)	EPS A1/268	240	500	39,7	23 x 94	50

(i) ergots décalés de 45° par rapport à l'axe du filament.

(1) Pins are schitted by 45° in regards of filament axis.