

GX5,3 : entraxe des pins de 5,3 mm / 5,3 mm pin spacing

GZ6,35 : entraxe des pins de 6,35 mm / 6,35 mm pin spacing


CODE STOCK PART NUMBER	RÉFÉRENCE	CODE ANSI	VOLTS	WATTS	TEMP. COUL. ° KEVIN	DISTANCE DE MONTAGE (MM)	DURÉE VIE AC LIFE
---------------------------	-----------	--------------	-------	-------	------------------------	-----------------------------	----------------------

GX5,3

130300	H 63180	EPT	10,8	42	2 900	-	8 000
130343	H 41860 WFL	BAB	12	20	3 100	40	2 000
132010	H 41870 MFL	ENL	12	50	3 100	50	2 000
131210	H 63159	DDL	20	150	3 150	200	500
131216	H 63165	DDS	21	80	3 125		1 000
130275	H 63113	EJA	21	150	3 350	28	40
130282	H 64653	ELC	24	250	3 400	30	50
130406	H 63196	ENX	82	360	3 300	300	75

GZ6,35

130264	H 164607	EFM	8	50	3 300	32	50
130266	H 164615	EFN	12	75	3 350	32	50
130269	H 164627	EFP	12	100	3 350	32	50
130259	H 161479	-	12	100	-	32	1 500
130270	H 164634	EFR	15	150	3 350	32	50



CODE STOCK PART NUMBER	RÉFÉRENCE	CODE ANSI	VOLTS	WATTS	TEMP. COUL. ° KEVIN	DISTANCE DE MONTAGE (MM)	DURÉE VIE AC LIFE
---------------------------	-----------	--------------	-------	-------	------------------------	-----------------------------	----------------------

130292	H 63154	DNF A1/226	21	150	3 400	70	25
130679	H 63155	ELZ	21	150	3 400	70	60
130294	H 63160	EMM/EKS	24	250	3 400	66	50
130298	H 63166	DNE	120	150	3 350	70	15